



EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB00000XH
Revision No:
2

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

That the Pitch indicator

with type designation(s)
Bridge Mate Propulsion Display

Issued to
Marine Technologies LLC
Egersund, Norway

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2020/1170**,
item No. MED/4.22. SOLAS 74 as amended, Regulations V/18, V/19 & X/3, IMO Res. A.694(17), IMO Res. MSC.36(63), IMO Res. MSC.97(73), IMO Res. MSC.191(79), IMO Res. MSC.302(87)


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-04-29**.

Issued at **Høvik** on **2021-04-30**

DNV local station:
Norway CMC, West

Approval Engineer:
Steinar Kristensen



Notified Body
No.: **0575**

for **DNV AS**

Sverre Olav Bergli
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Bridge Mate Propulsion Display Pitch Indicator consists of the below modules:

Unit	Component	Note
Computer	MT-COMPUTER-300 <i>or</i>	Computer with on-board DVI interface
	MT-COMPUTER-400	
Display	Hatteland HD 13T21 MMD <i>or</i>	DVI interface
	Hatteland HD 17T22 MMD	
Network switches	Netgear GS728TP <i>or</i>	24 ports, 10/100/1000Mbs, PoE, RJ 45
	MT-PoE—SWITCH-1080-8-PORT <i>or</i>	8 ports, 10/100/1000Mbs, PoE, RJ 45
	ORing IGPS-1080-24V	8 ports, 10/100/1000Mbs, PoE, RJ 45
I/O Interface units	MT IOB mK2 (I/O card) <i>or</i>	Listener according to IEC 61162-1 and IEC 61162-2
	MT-PoE-IOB (I/O card)	Thruster/Rudder Interface: $\pm 10V$ and 4-20mA Listener and talker according to IEC 61162-1 and IEC 61162-2
Options		
NMEA-CONVERTER	MT-NMEA-CONVERTER	Listener and talker according to IEC 61162-1 and IEC 61162-2
Input Device	Keyboard Cherry / MT Type	

All units listed above are to be installed in a protected environment, i.e. indoor.

Software modules

- | | Version |
|-----------------------------------|-------------------------------------|
| • Operating System: | Windows 8.1 Industrial Pro Embedded |
| • Bridge Mate Propulsion Display: | 1.6.x.x |

Application/Limitation

- Bridge Mate Propulsion Display Pitch Indicator is be connected to transmitters with output signal 4-20mA or $\pm 0-10VDC$, and which meet the requirements for transmitters in ISO 22555.
- The Propulsion Display may display Thrust as a combination of RPM and Pitch
- The Bridge Mate Propulsion Display is restricted to be used in MT Bridge Mate applications
- The Bridge Mate Propulsion Display does not issue alerts, hence testing according to IEC 62923-1 and IEC 62923-2 is deemed as not being applicable.

Type Examination documentation

DNV No	Document ID	Rev.	Description
36	141011F	2014-03-11	Report: TesLab, EMC and environmental test report for Netgear GS728TP
35	MRA0000006	2	Certificate: DNV, EU-MR-TA certificate for Maritime Multi Displays and Standard Displays – Series X
34	1907-2-29-IGPS-1080-1	V1.1	Manual: ORing, Quick Installation Guide for IGPS-1080-24V
32	202-11136-01	V1.0	Manual: Netgear, Netgear GS728TP Hardware Installation Guide
31	MT-DEV-5648	1.0	Manual: MT, Installation Manual MT-COMPUTER-300 WINDOWS 8.1
29	MT-DEV-5469	1.0	Manual: MT, Maintenance manual for computer based systems
28	MT-DEV-0683	7.0	Manual: MT, Overhead Indicator Display, User and Technical Manual
27	MT-DEV-5653	2.0	Manual: MT, Installation manual MT-COMPUTER-400 Operating Systems
26	INB101192-1	16	Manual: Hatteland, User Manual- Series X G2 Maritime Multi Display (MMD) models
20	17A284F	2018-01-25	Report: TesLab, EMC and environmental test report for MT-COMPUTER-400
19	17A283F	2018-01-25	Report: TesLab, EMC and environmental test report for MT-COMPUTER-300

DNV No	Document ID	Rev.	Description
18	MRA0000016	2	Certificate: DNV, Hatteland HD XXT22 MMD Monitor series
16	147124F	2014-09-15	Report: TesLab, NMEA CONV IEC 60945 report
15	MT-DEV-5457	0.7	Report: MT, IEC 61162-1 and -450 MT NMEA Converter Test Program
13	DOC206405-1	R01	Report: Hatteland, Conformance test report HD 19T22 MMD-MA1-FAGA HTB30-DVI-D
12	DOC206081-1	R01	Report: Hatteland, IEC 62288 flicker test report HD 19T22 MMD
11	DOC206452-1	R01	Report: Hatteland, Conformance test report HD 17T22 MMD-MA1-FAGA HTB30-DVI-D
10	DOC206444-1	R01	Report: Hatteland, IEC 62288 flicker test report HD 17T22 MMD R01
9	T140319D03-RL	00	Report: CCS, Environmental Test Report ORing-IGPS-1080-24V / MT-PoE—SWITCH-1080-8-PORT
8	T140319D03-E	2014-03-24	Report: CCS, EMC Test Report ORing-IGPS-1080-24V MT-PoE—SWITCH-1080-8-PORT
4	MT-DEV-0683	5.5	Manual: MT, Operations Manual Overhead panels
2	MT-DEV-5460	2016-03-21	Report: MT, Propulsion Display Test Report

Tests carried out

- Performance testing: ISO 22555 (2007)
- Environmental testing: IEC 60945 (2002) incl. Corr.1 (2008)
- Presentation of navigation information: IEC 62288 (2014)
- Serial interface testing: IEC 61162-1 (2016) and IEC 61162-2 (1998)

Marking of product

The type designation and name and contact address of the manufacturer shall be affixed visibly, legibly and indelibly to the product. In addition the product shall be marked with serial number, safe distance to magnetic compass, power consumption and/or supply voltage.